

Casco Contact



Suitable for floor – and wall substrates of vinyl and PVC carpet, PVC-free carpet, rubber, linoleum, cork, laminate, leather, textile, metal and styrofoam.

Note! Does not bond to brass or copper.

- Water based
- Odourless
- High bonding strength
- Easy to apply
- For absorbent and non-absorbent substrates
- Suitable for floor heating
- Suitable for castor wheels
- Heat re-active up to 5 days

TECHNICAL DATA

Basis: Superior polymer dispersion

Appearance: Crème coloured

Consistency: viscous and thixotrope

Density: Approx. 1360 kg/m³

pH: 7

Solvent: water

Storage time: at least 12 months in room temperature (not below +5°C, sensitive to frost)

Flash point: > 100°C, not applicable

All information is based on approx. 20°C and 65% relative air humidity.

APPLICATION DATA

Working temperature: +15°C - +25°C

Consumption: 2 - 4 m²/l (300 - 700 g/m²) depending on the substrate

Application time: 30 min to 4h

Walkable: immediately

Tools: Roller, plain trowel or paint brush.

DIRECTIONS FOR USE

Substrates must be permanently dry, solid, level and free from cracks, dirt and adhesion-inhibiting substances. Use a suitable levelling compound to level out uneven subfloors and substrates.

Old existing floor coverings, such as tile, coatings, etc., must be thoroughly cleaned (degreased) and visibly sanded.

SURFACE PREPARATION

The substrate to be glued must be free from dirt and adhesion-inhibiting substances. If necessary, clean the backside of the substrate before applying the adhesive.

APPLICATION

Apply generously and evenly on the backside of the material to be glued, as well as on the subfloor with a suitable tool, such as a roller, brush or trowel. Avoid formation of adhesive puddles. After the adhesive has dried, put the two substrates together and press thoroughly.

If corrections are needed of the substrate, it is possible to do after heating, for example with hot air blower. It is possible to heat re-activate up to 5 days after the adhesive has dried.

The laid flooring is immediately suitable for walking.

Important

Do not use at temperatures below +15°C. In cold weather, warm up the adhesive in due time in heated room. Frost sensitive.

CLEANING

Wet adhesive is easily washed off with water. Dry adhesive is mechanically removed or with use of Casco Brutal Wipes.

Avoid eye and skin contact. If eyes are contaminated, rinse thoroughly with large amounts of water. Clean skin with soap and water.



KEEP OUT AF REACH OF CHILDREN.

For additional health and safety information consult the Safety Data Sheet.

DISPOSAL

Empty bags completely and dispose in accordance with local regulations.

For disposal of product residues, waste water and containers with adherent product residues, follow local governmental regulations.

CERTIFICATE

Casco Contact is certified according to EMICODE EC1 PLUS.



PACKAGES

1 liter
5,5 liter

ENVIRONMENTAL ASPECTS

No labelling or risk phrases.

Informationen är baserad på laboratorieutredningar och lång praktisk erfarenhet. Uppgifterna är orienterande och avser att hjälpa förbrukaren att finna den lämpligaste arbetsmetoden. Eftersom förbrukarens produktions- förhållanden ligger utanför vår kontroll, kan vi inte ansvara för arbetsresultat, påverkade av lokala omständigheter. I varje enskilt fall rekommenderas provning och kontinuerlig kontroll

Certifierad enligt:



Sika Sverige AB
163 08 Spånga, Sverige
Tel: +46 8 621 89 00
Web: www.casco.com