



Replaces: 2013-09-06

Date: 2014-10-08

## Glutolin Normal

Used for special paper wall coverings with sensitive prints in dry areas. Ideal for use if you are over-sensitive or allergic to preservatives.

- Powder-based cellulose wallpaper paste
- Fast-dissolving
- Highly economical
- High bonding strength
- No preservatives

### TECHNICAL DATA

**Type:** Methyl cellulose

**Colour:** White powder; mixed – transparent

**Consistency:** Thixotropic (mixed with water)

**Density:** Approx. 350 kg/m<sup>3</sup>

**Dry content:** 7.5–9% mixed, depending on the quality of the water

**Fire hazard:** No

**Durability:** The dried adhesive is not water resistant

### APPLICATION DATA

**Work temperature:** Not below +18°C – both surface and material.

**Mixing:** Mix the powder with water to produce a homogeneous, lump-free mixture. Leave to mature for 3–5 minutes. Ready to use.

**Material consumption:**

- Pre-gluing – 125 grams of powder to 10 litres of water, sufficient for approx. 75 m<sup>2</sup>
- Light wallpaper – 125 grams of powder to 7.5 litres of water, sufficient for approx. 40 m<sup>2</sup>
- Heavier wallpaper – 125 grams of powder to 6.2 litres of water, sufficient for approx. 35 m<sup>2</sup>

**Application time:** 5–20 minutes

**Storage time:** 12 months (in unopened packaging). Store in a cool, frost-free place.

### HEALTH AND THE ENVIRONMENT

#### Handling and cleaning instructions

Observe good work hygiene. On contact with the skin, wash the adhesive off with soap and water. Clean tools with water before the adhesive dries. Use methylated spirits to dissolve dry adhesive.

For additional information, see the Safety Data Sheet.

### INSTRUCTIONS FOR USE

Remove any loose paper wall covering, fill or remove any loose-sitting mesh. Sand painted surfaces and wash with 5% ammonia solution/universal cleaner; then rinse with water. Tape over joins and fill any irregularities. Pre-treat weak surfaces or strongly absorbent underlay with a mixture of 1 part adhesive to 80 parts water.

Glutolin Normal can be applied directly to wallpaper or the wall surface. Take care to use the right volume and correct mixing ratio. Follow the instructions from the wallpaper producer. Glutolin Normal bonds strongly to both wallpaper and the underlying surface, so the lengths of wallpaper will be hard to adjust when hanging.

### PACKAGING

125 gram



---

This information is based on laboratory reports and extensive practical experience. The information is intended for users and designed to help them identify the most appropriate work method.  
As the production conditions of the individual user is beyond our control, we accept no liability for the actual result of the work, affected by local circumstances. In every case, we recommend testing and ongoing checks

---

**Certified according to:**



**Sika Sverige AB**  
163 08 Spånga, Sweden  
Tel. +46 8 621 79 00  
Web: [www.casco.com](http://www.casco.com)