



Replaces: 2011-05-30

Date: 2014-10-08

Kontaktlim Förtunning

Solution of thinner, intended for diluting contact adhesive, cleaning tools, removing glue stains, etc.

- Clear, transparent colour
- Not sensitive to cold

TECHNICAL DATA

Type: Mixture of solvents

Colour: Transparent

Consistency: Highly liquid

Density: Approx. 758 kg/m³

Solvents: Heptane and ethyl acetate

Fire hazard: Fire class 1

Temperature sensitivity: Not sensitive to cold

For additional information, see the Safety Data Sheet.

PACKAGING

5 litres

1 litre

APPLICATION DATA

Diluting adhesive: When diluting Contact Adhesive S9 Super for spraying, use 10–14% KontaktlimFörtunning (Contact Adhesive Thinner).

Storage time: Unlimited in sealed packaging. Store in a cool, frost-free place.

HEALTH AND THE ENVIRONMENT

Labelling

Highly flammable. Hazardous on inhalation, skin contact and ingestion. Store out of the reach of children. Store well away from sources of ignition. No smoking. Good ventilation essential. Do not dispose of in public drains. Take measures to guard against static electricity. Contains toluene and heptanes.

Handling and cleaning instructions

Avoid open flames and sparks. Use suitable gloves and goggles.



This information is based on laboratory reports and extensive practical experience. The information is intended for users and designed to help them identify the most appropriate work method.
As the production conditions of the individual user is beyond our control, we accept no liability for the actual result of the work, affected by local circumstances. In every case, we recommend testing and ongoing checks

Certified according to:



REG. NO. 31982

Sika Sverige AB
163 08 Spånga, Sweden
Tel. +46 8 621 79 00
Web: www.casco.com