

## PRODUCT DATA SHEET

# CascoProff TexFix

FLOOR ADHESIVE FOR SIMPLIFYING REMOVAL OF THE COVERING IN THE FUTURE, FOR EXAMPLE WHEN RENOVATING THE FLOOR.



### DESCRIPTION

Solvent-free adhesive for floor-coverings, to simplify removing the covering in the future.  
Recommended for fixing textilecoverings with various backings.  
For indoor use only.

### USES

Fixing textile coverings with various backings.

### CHARACTERISTICS / ADVANTAGES

- Easy to apply
- Suitable on floor heating systems
- Solvent and APEO free
- High initial tack and peel strength.
- Water-removable from subfloor
- Suitable for castor wheels

### PRODUCT INFORMATION

|                                |                                                                                                                                                                                          |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Composition</b>             | Acrylic- copolymer dispersion                                                                                                                                                            |
| <b>Packaging</b>               | 10 liter                                                                                                                                                                                 |
| <b>Colour</b>                  | Light colour                                                                                                                                                                             |
| <b>Shelf life</b>              | 1 year in closed containers.                                                                                                                                                             |
| <b>Storage conditions</b>      | Should not be exposed to temperatures below 0 °C and above +30 °C. If there is skin formation, remove this, do not mix in to the product. Opened containers should be closed immediately |
| <b>Density</b>                 | Appr. 1300 kg/m <sup>3</sup>                                                                                                                                                             |
| <b>Solid content by weight</b> | Appr. 75 %                                                                                                                                                                               |
| <b>Viscosity</b>               | Appr. 19 000 – 25 000 mPa.s, Brookfield RVT, sp 6, 20 rpm, 20 °C                                                                                                                         |

## APPLICATION INFORMATION

|                                |                                                                                                               |
|--------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Consumption</b>             | 1 liter / 6 - 8 m <sup>2</sup>                                                                                |
| <b>Ambient Air Temperature</b> | min +18 °C - +25 °C and 20–70 % RH. The climate must be maintained for at least 96 h (4d) for optimal result. |
| <b>Application Time</b>        | Approx. 20 min. depending on temperature and humid.                                                           |

## APPLICATION INSTRUCTIONS

When using CascoProff TexFix on new produced concrete we recommend minimum 10 mm self leveling compound.

### ON NON-POROUS SUBFLOORS

1. Spread the adhesive with a roller or brush. Don't use more adhesive than necessary to give a good over-wetting during the stated open time.
2. Install material at once or after a very short open time and rub thoroughly to press out all the air and achieve a good contact between the adhesive and the covering, for best result use a carpet roller.
3. Check that the whole covering area has full contact with the adhesive.

**NOTE !** If applied on a non-absorbent subfloor, the adhesive shall be diluted with 1 part water to 10 parts adhesive.

### ON POROUS SUBFLOORS

Create an non absorbent surface by priming with suitable Casco primer, allowed to dry completely.

### RE-INSTALLATION

Release coating in a corner and pull gently. Possible residual adhesive is dissolved with warm water containing 2 % detergent. Allow the mixture to work for 15-20 minutes, after which the remainings are scraped off.

### SUBSTRATE PREPARATION

Before installing the covering make sure that the subfloor is clean, even and dust free and has an adequate strength, bearing strength, dimensional stability and is permanent dry.

The moisture content in the concrete must not exceed 85 % RH and the chipboard moisture quota should be 8-12 %.

#### Sika Sverige AB

Domnarvsgatan 15  
Box 8061  
SE- 163 08 Spånga Sweden  
TEL: +46 8 621 89 00  
info@se.sika.com  
www.casco.eu

## CLEANING OF EQUIPMENT

Clean application tools with water before the adhesive has dried. Dried adhesive is dissolved in ethanol.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website [www.casco.eu](http://www.casco.eu).

CascoProffTexFix-en-SECASCO-(03-2020)-1-1.pdf

#### PRODUCT DATA SHEET

CascoProff TexFix  
March 2020, Version 01.01  
020512030110000017