


# PRODUCT DATA SHEET

# RR

FINE GRAINED, FAST DRYING, STRONG AND SHAPABLE STURDY MORTAR.



## DESCRIPTION

Fine grained, fast drying, strong and shapable sturdy mortar. Suitable on substrates like concrete, cement, gypsum, wood, tiles etc, layer thickness up to 50 mm.

## USES

Suitable on substrates like concrete, cement, gypsum, wood, tiles etc, layer thickness up to 50 mm.

## CHARACTERISTICS / ADVANTAGES

- Fine-grained
- Able to shape
- Free of cracks even in thicker layer
- Fast drying independent of the layer thickness
- Suitable for applications on subfloor heating system.

## APPROVALS / CERTIFICATES

## PRODUCT INFORMATION

<b>Composition</b>	Cement based
<b>Packaging</b>	15 kg
<b>Shelf life</b>	Storage life 6 month (in closed packaging). Opened bags should be closed immediately and used up as soon as possible.
<b>Storage conditions</b>	Store RR in cool, dry conditions.
<b>Bulk Density</b>	1,42 kg/liter of dry powder

## APPLICATION INFORMATION

<b>Consumption</b>	approx. 1,6 kg/m <sup>2</sup> /mm
<b>Layer Thickness</b>	1-10 mm (10-50 mm extended with sand)
<b>Substrate Temperature</b>	Both substrate and leveling compound: Not below +5 °C, best conditions between +15 °C - +20 °C
<b>Pot Life</b>	approx. 15 minutes
<b>Waiting Time / Overcoating</b>	Walk-able: approx. 0,5 hours Cover-able: approx. 4 hours

# APPLICATION INSTRUCTIONS

## MIXING

- 15 kg of RR / 3,3 liter of cold water
- Extended levelling compound (above 10 mm thickness) The additive is added last.
- Layer thickness of 10 to 20 mm: mix 15 kg Casco Floor Expert RR with 3,6 liter of water + 9,6 kg of sand (0-3mm).
- Layer thickness of 20 to 50 mm: mix 15 kg Casco Floor Expert RR with 3,6 liter of water + 15 kg of sand (0-8 mm).

## APPLICATION

RR is suitable for filling, repairing, leveling and making slopes:

- For fast full-surface smoothing of the subfloors
- Of staircase and wall projections.
- To level out differences in height to adjacent areas
- As a repairing mortar for filling holes and deepening.
- Can be used under textile, ceramic and elastic coverings.
- For indoor use only.
- The leveling compound must be covered.

## PRIMING

For priming the substrates, use suitable Casco Floor Expert primer. For further information see technical data sheet of the primer.

## RECOMMENDED METHOD OF WORKING

- Using a clean bucket.
- Pour RR into cold, clean water and stir to a homogenous mixture (speed mixer recommended, 600 rpm, 3 min)
- Spread, smooth and model the levelling compound with a smoothing trowel or spatula.
- Protect curing RR from high ambient temperatures, direct sunlight and draughts.
- Clean tools with water.

## SUBSTRATE PREPARATION

### REQUIREMENTS OF SUBSTRATE

- Adequate strength, bearing strength, dimensional stability and permanent dry.
- Free of layers which reduce adhesion, e.g. dust, dirt, oil, fat, wax cleaning agents and loose particles.
- Separation layers, sinter layers, and other similar contamination should be removed through sanding, brushing, abrasive blast cleaning, milling or thorough cleaning.
- Old, loose and weak levelling layers should be removed mechanically.

- When installing floor coverings, the RH of the construction must not exceed 85 %.
- Layers of water-soluble adhesives, e.g. sulphite adhesives, should be removed completely.
- Old water-resistant adhesives should be mechanically removed as thoroughly as possible.
- Old floors, such as ceramic tiles are to be thoroughly cleaned and sanded.
- OSB to be grinded intensively.
- Rooms that do not have a cellar underneath must be sealed against rising dampness in compliance with the standard.
- The requirements specified in relevant valid standards, guidelines and specifications must be fulfilled.

## SUBSTRATE QUALITY

### RR is suitable on substrates like:

- Concrete
- Light concrete
- Cement and rapid cement screeds
- Mastic asphalt screeds (sanded) IC 10 and IC 15 according to EN 13 813
- Old substrates such as ceramic tiles, natural stones and terrazzo
- Wooden substrates
- Gypsum boards.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

### PRODUCT DATA SHEET

RR

March 2020, Version 01.01  
020815030110000012

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website [www.casco.eu](http://www.casco.eu).

### **Sika Sverige AB**

Domnarvsgatan 15  
Box 8061  
SE- 163 08 Spånga Sweden  
TEL: +46 8 621 89 00  
[info@se.sika.com](mailto:info@se.sika.com)  
[www.casco.eu](http://www.casco.eu)

### **PRODUCT DATA SHEET**

RR  
March 2020, Version 01.01  
020815030110000012