

## PRODUCT DATA SHEET

# CascoSpack S

READY-MIXED, QUICK-DRYING LATEX FILLER FOR JOINERY.



### DESCRIPTION

Ready-mixed, quick-drying latex filler for joinery. For filling holes and broad filling of small surfaces indoors. Very good bonding to most construction materials. For dry rooms.

### USES

- Filler for joinery.
- Filling of holes and broad filling of small surfaces.
- Very good bonding to most construction materials.
- Indoor use.
- For dry rooms.

### CHARACTERISTICS / ADVANTAGES

- Quick-drying
- White

### PRODUCT INFORMATION

Composition	Dispersionbased filler
Packaging	400 ml
Appearance / Colour	White paste
Shelf life	12 months (in unopened packaging)
Storage conditions	Store in a cool, frost-free place
Density	1,8 kg/m <sup>3</sup>

### APPLICATION INFORMATION

Consumption	1 litre/m <sup>2</sup> /mm
Layer Thickness	up to 2 mm
Substrate Temperature	Not below +18°C

## APPLICATION INSTRUCTIONS

- Make sure the underlying surface is clean, dry and firm.
- Even out any irregularities with filler.
- Leave to dry and then sand the surface smooth.
- Dust-free surfaces can be painted with latex/acrylic paint.
- Use water to clean tools.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website [www.casco.eu](http://www.casco.eu).

### Sika Sverige AB

Domnarvsgatan 15  
Box 8061  
SE- 163 08 Spånga Sweden  
TEL: +46 8 621 89 00  
[info@se.sika.com](mailto:info@se.sika.com)  
[www.casco.eu](http://www.casco.eu)

### PRODUCT DATA SHEET

CascoSpack S  
May 2020, Version 01.01  
021840303000000019