



A SIKA BRAND

PRODUCT DATA SHEET

CascoSpack Universal

READY-MIXED WALL LEVELLING COMPOUND WITH EXTRA FINE SURFACE AND HIGH FILLING CAPACITY. ALSO ROLLABLE.



DESCRIPTION

Ready-mixed wall levelling compound with extra fine surface and high filling capacity. Very easy to apply and has low shrinkage. For full surface levelling and small repairs on concrete, light concrete, wood etc. Ideal for applying joint tape. Can also be applied by roller. To be painted or used as underlay for wallpaper, mesh, panels, etc. For dry rooms.

USES

- Full surface levelling.
- Rollable after mixing 1-2 min.
- Repairs up to 4 mm.
- Applying paper stripes
- Use for as underlay for wallpaper, mesh, panels, paint etc.
- For dry rooms.

CHARACTERISTICS / ADVANTAGES

- Extremely easy to apply
- Very fine grain with excellent filling capacity
- Very smooth surface and easy to sand
- Short drying time
- For small repairs and full surface levelling
- Rollable after mixing

APPROVALS / CERTIFICATES

Fulfill the requirements of CE-marking according to EN 15824 and EN 13963.

PRODUCT INFORMATION

Composition	Pasty filler based on calcium
Packaging	10, 5 litres and 250 ml

PRODUCT DATA SHEET
CascoSpack Universal
May 2020, Version 02.01
021840103000000023

Appearance / Colour	Light grey
Shelf life	12 months (in unopened packaging).
Storage conditions	Store in a cool, frost-free place.
Density	Approx. 1,35 kg/l

APPLICATION INFORMATION

Consumption	1 litre/m ² /mm
Layer Thickness	Up to 4 mm/layer
Substrate Temperature	Not below +5°C
Drying time	1–2 hours, depending on layer thickness

APPLICATION INSTRUCTIONS

- The product can be used on material such as gypsum boards, wood, concrete, light concrete, particle board etc. for small repairs (up to 4 mm) and for full surface levelling. Holes deeper than 4 mm need to be filled several times, with sufficient drying time between applications.
- The product is rollable if mixed for 1-2 minutes. Do not add any water!
- If used on surfaces like fibreglas coverings, the product needs to be applied twice.
- The product can be over painted or be used as underlay for wallpaper.

Levelling

Before you start levelling, make sure the surfaces are clean, dry and free from loose particles. Use a steel trowel and hold the trowel in an angle of approx 30° to the wall. Do not press too hard and apply the levelling compound with large strokes. After each levelling, sand the surface with a fine sandpaper once the filler has dried. Make sure to also clean the wall with a dry brush or cloth before applying the next layer of levelling compound, wallpaper or paint.

If wallpaper will be applied to the wall, make sure to pre-glue the wall with diluted wallpaper adhesive (see label of wall adhesive for instructions how to dilute), to secure a good bond and to reduce the risk of blisters.

The product is only intended for indoor use in dry areas.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Sika Sverige AB

Domnarvsgatan 15

SE-163 08

Spånga Sweden

LOCAL RESTRICTIONS
Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

PRODUCT DATA SHEET

CascoSpack Universal
May 2020, Version 02.01
021840103000000023