



Replaces: 2011-05-09

Date: 2017-03-31

Casco Tapetstrip

Water based dispersion for losing most old wallpaper and non-woven. Not for fiberglass.

- Water based
- No alkali
- Easy to apply with roller, brush or sponge

TECHNICAL DATA

Basis: Polyvinylacetat dispersion and starchderivat.

Colour : Transperent.

Consistency: Thin

Density: Ca 1000 kg/m³.

Dry content: 14 %.

Flammability: No risk

Solvent: Water

pH: Ca 6.

APPLICATION DATA

Working conditions: not below +5°C in both the substrate and the material.

Before use: Mix 250 ml Tapetstrip with 5 liter water before use.

Tool: roller, brush or sponge.

Waiting time: Approx. 15 – 20 min depending on temperature and humidity.

Storage time: 12 months (in unopened package). Store in dry and cool condition. May not be exposed to temperatures below +5°C or above +30°C.

SAFETY AND ENVIRONMENT

Handling and Cleaning Instructions

Observe good industrial hygiene. Therefore, make sure to always work carefully and systematically to avoid unnecessary waste.

In case of skin contact, wash with soap and water.

For further information see Safety data sheet, classification, composition and properties.

RECOMMENDED METHOD OF WORKING

Protect the floor under need

Tear away as much lose wallpaper you manage before apply tapetstrip. Use a piggroller to perform the surface on the wallpaper.

Apply abundant of ready mix Tapetstrip with a sponge, bruch or roller. Wait 15-20 min before you tear down wallpaper with a metal toothed trowel. Replay again if you don't get all wallpaper lose from the surface.

PACKAGING

0,75 liter



Informationen är baserad på laboratorieutredningar och lång praktisk erfarenhet. Uppgifterna är orienterande och avser att hjälpa förbrukaren att finna den lämpligaste arbetsmetoden. Eftersom förbrukarens produktions- förhållanden ligger utanför vår kontroll, kan vi inte ansvara för arbetsresultat, påverkade av lokala omständigheter. I varje enskilt fall rekommenderas provning och kontinuerlig kontroll

Certifierad enligt:



Sika Norge AS
Postadresse:
Postboks 71
2026 SKJETTEN
Tel: +47 67 06 10 90
Web: www.casco.no