

## WETSTOP MG-L



WETSTOP MG-L is a self-adhering butyl rubber coated non-woven line drain sealing cuff with release overlaps for easy removal. In combination with CASCO water membranes intended for sealing the penetrations around the line drains with a plastic or metal flange. Approved according ETAG 022 as a kit component in watertight covering kits of CASCO WETSTOP and CASCO AQUASTOP. For interior use.

- Approved according ETAG 022 as a kit component
- EC1 Plus: very low emission
- Self-adhering
- Crack bridging
- Watertight
- Waterproof
- Suitable on heated floor
- Good adhesion to CASCO water membranes

### TECHNICAL DATA

**Dimensions:** 250 mm x 1500 mm

**Material thickness:** ~ 0,7 mm

**Colour:** blue

**Temperature resistance:** -20°C to +60°C

**Packaging:** 4 pcs./carton

**Storage:** 12 months in cool, dry conditions, protect against sunlight

### APPLICATIONS

WETSTOP MG-L in combination with CASCO water membranes is suitable:

- in private wet rooms: bathrooms and shower rooms
- in highly loaded public wet rooms: shower rooms in the sports facilities, hospitals, therapy rooms
- in laundry rooms
- in toilets
- on heated floor
- in interior areas

### SUBSTRATE AND PREPARATION

#### normal absorbent substrates

- concrete
- cement screeds
- cement plaster
- lime-cement plaster
- gypsum boards

prime with CASCO PRIMER (1:3)

#### calcium sulphate substrates

- calcium sulphate screeds
  - gypsum plaster
- prime with CASCO PRIMER (1:1)

### non-absorbent substrates

- ceramic coverings, stable, thoroughly cleaned and if necessary abraded  
priming not required

### REQUIREMENTS OF THE SUBSTRATES

The substrate should be sufficiently sound, loadable, solid and free of dust, dirt, oil, grease and interfering agents. Remove parting and sinter layers by appropriate measures. Old ceramic covering surfaces must be thoroughly cleaned and abraded if necessary. Gypsum plasters (according EN 13279-1) should have a residual moisture of  $\leq 75\%$  RH. Cement-based screeds (28 days old):  $\leq 85\%$  RH, cement-based screeds (heated):  $\leq 75\%$  RH, calcium sulphate screeds must have residual moisture of  $\leq 75\%$  RH, as floor heating screed  $\leq 65\%$  RH. Observe country-specific guidelines. Uneven substrates must be smoothed with the appropriate CASCO levelling compound as required.

### RECOMMENDED METHOD OF WORKING

WETSTOP MG-L is used for sealing the penetrations prior the membrane application in the entire area.

At first install one side of WETSTOP MG-L sealing cuff on the surface by removing release liner. After install the other side of WETSTOP MG-L by carefully removing release liner. Ensure that WETSTOP MG-L is installed wrinkle free. For pressing in WETSTOP MG-L use a blunt smoothing trowel or spatula.

While connecting WETSTOP MG-L to different sealing accessories or foil membrane CASCO WETSTOP, ensure minimum 5 cm overlapping.

Water membrane in the entire surface could be applied



directly after WETSTOP MG-L installation.

Cover completely the top surface of WETSTOP MG-L with CASCO water membrane, which is used in the entire surface area. In case of WETSTOP MG-L is used in combination with CASCO WETSTOP water membrane, cover completely the surface of WETSTOP MG-L with CASCO WETSTOP iFIX or WETSTOP FOIL SEAL.

#### IMPORTANT

Pay attention to the product data sheet of the chosen CASCO water membrane. Follow the relevant product data sheet when using the complementary products.

#### DISPOSAL

Dispose of in accordance with the regulations. For disposal of product residues, washing water and containers with adherent product residues please, follow the local governmental regulations.

#### ENVIRONMENTAL APPROVALS

EMICODE EC1 PLUS

---

We guarantee that our products leave the factory in perfect condition. While our recommendations for use are based on tests and practical experience, they can only provide general guidance without any assurance as to product characteristics, since we have no influence over the conditions on site, the execution of the work or the method of processing. This product data sheet supersedes all previous editions.

---

Sika Sverige AB  
163 08 Spånga, Sverige  
Tel: +46 8 621 89 00  
Web: [www.casco.com](http://www.casco.com)