



---

DECLARATION OF PERFORMANCE  
according annex III of the regulation (EU) No. 305/2011

for the product

**CASCO MULTIFILL**

No. 118041001

---

1. Unique identification code of the product type  
**Spackel Vát**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR  
**batch number: see packaging of the product**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer  
**Joint filling and wide spreading of internal surfaces in accordance with EN 15824 "Specifications for external and internal plasters based on organic binders" and EN 13963 "Jointing materials for gypsum platerboards"**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR  
**Sika Deutschland GmbH  
Niederlassung Rosendahl  
Alfred-Nobel-Str. 6  
48720 Rosendahl / Germany**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)  
**not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V  
**Systeme 3 EN 15824 and system 4 EN 13963**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard  
**EN 15824: The notified body 0402 performed the determination of reaction to fire class on the basis of type testing under sytem 3 and issued: Classification report  
EN 13963: The Casco Schönox Sweden AB performed the classification regarding reaction to fire according to system 4 on the basis of resolution 2010/83/EU of the EU Commission**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued  
**not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Bond strength	> 0,3 Mpa	EN 15824:2009
Reaction to fire class	F	EN 15824:2009
Flexural strength	> 320 N	EN 15824:2009

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Rosendahl, 2018-04-10



Wolfgang Börsting, R&D Manager



Felix Meinert, R&D Lab Manager  
MTC

According Article 6(5) of the regulation (EU) No. 305/2011 an MSDS, conform to (EU) No. 1907/2006 (REACH) annex II, is attached to this Declaration of Conformity.