



DECLARATION OF PERFORMANCE
according annex III of the regulation (EU) No. 305/2011

for the product

MULTIFIX

No. 116060602

1. Unique identification code of the product type
EN 12004: C2 TE

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR
batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer
Improved cementitious adhesive for tiling

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR
**Sika Deutschland GmbH
Niederlassung Rosendahl
Alfred-Nobel-Str. 6
48720 Rosendahl / Germany**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)
not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V
Systeme 3 / Systeme 3 fire resistance

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard
The notified body 0992 carried out the determination of the product type on the basis of type testing under sytem 3 and issued: test report. The notified body 1378 performed the determination of reaction to fire class on the basis of type testing under sytem 3 and issued: Classification report

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued
not applicable

9. Declared performance

| Essential characteristics | Performance | Harmonized technical specification |
|--|-------------------------|------------------------------------|
| Reaction to fire class | A1 / A1 _{fl} | 12004:2002 |
| Early tensile adhesion strength | n.a. | 12004:2002 |
| Initial tensile adhesion strength | ≥ 1,0 N/mm ² | 12004:2002 |
| Tensile adhesion strength after water immersion | ≥ 1,0 N/mm ² | 12004:2002 |
| Tensile adhesion strength after heat ageing | ≥ 1,0 N/mm ² | 12004:2002 |
| Tensile adhesion strength after freeze-thaw cycles | ≥ 1,0 N/mm ² | 12004:2002 |
| Release of dangerous substances | See MSDS | 12004:2002 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Rosendahl, 2017-02-03



Wolfgang Börsting, R&D Manager



Felix Meinert, R&D Lab Manager
MTC

According Article 6(5) of the regulation (EU) No. 305/2011 an MSDS, conform to (EU) No. 1907/2006 (REACH) annex II, is attached to this Declaration of Conformity.