



---

DECLARATION OF PERFORMANCE  
according annex III of the regulation (EU) No. 305/2011

for the product

## **SCHÖNOX PFK WHITE**

No. 112092110

---

1. Unique identification code of the product type  
**EN 12004: C2 TE S1**
  
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR  
**batch number: see packaging of the product**
  
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer  
**Improved cementitious adhesive for tiling**
  
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR  
**Sika Deutschland GmbH  
Niederlassung Rosendahl  
Alfred-Nobel-Str. 6  
48720 Rosendahl / Germany**
  
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)  
**not applicable**
  
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V  
**Systeme 3 / Systeme 3 fire resistance**
  
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard  
**The notified body 0799 carried out the determination of the product type on the basis of type testing under sytem 3 and issued: test report. The notified body 1378 performed the determination of reaction to fire class on the basis of type testing under sytem 3 and issued: Classification report**
  
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued  
**not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire class	A1 / A1 <sub>fl</sub>	12004:2007+A1:2012
Early tensile adhesion strength	n.a.	12004:2007+A1:2012
Initial tensile adhesion strength	≥ 1,0 N/mm <sup>2</sup>	12004:2007+A1:2012
Tensile adhesion strength after water immersion	≥ 1,0 N/mm <sup>2</sup>	12004:2007+A1:2012
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm <sup>2</sup>	12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm <sup>2</sup>	12004:2007+A1:2012
Release of dangerous substances	See MSDS	12004:2007+A1:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Rosendahl, 2017-01-24



Wolfgang Börsting, R&D Manager



Felix Meinert, R&D Lab Manager  
MTC

According Article 6(5) of the regulation (EU) No. 305/2011 an MSDS, conform to (EU) No. 1907/2006 (REACH) annex II, is attached to this Declaration of Conformity.