

## Substrate Preparation

Substrate (for example)	Trockenestrich NORIT - TE		
Primer(for example)	SCHÖNOX VD		
Self levelling compound(for example)	SCHÖNOX HS 10	SCHÖNOX HS 50	SCHÖNOX HS10 F

## Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m <sup>2</sup>	Remark
<b>Stabparkett</b>				
	<b>SCHÖNOX® iLINE®</b> shear-elastic, waterless special adhesive for parquet	SCHÖNOX iLINE APP	ca. 800 g/m <sup>2</sup>	*
	<b>SCHÖNOX® iLINE HYBRID</b>	SCHÖNOX iLINE HYBRID AP SCHÖNOX iLINE HYBRID HP	ca. 600 - 650 g/m <sup>2</sup>	* zu Formaten Informationen einholen
	<b>SCHÖNOX® PARKETT 600</b> waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	ca. 1000 -1300 g/m <sup>2</sup>	*
	<b>SCHÖNOX® PARKETT 400</b> Universal wood adhesive for all kind of wood	B11 - B15	ca. 1000 -1200 g/m <sup>2</sup>	*
<b>Mosaikparkett</b>				Remark
	<b>SCHÖNOX® PARKETT 600</b> waterless universal SMP adhesive with hard glue-line for parquet	B6	ca. 800 g/m <sup>2</sup>	*
	<b>SCHÖNOX® PARKETT 400</b> Universal wood adhesive for all kind of wood	B6	ca. 800 g/m <sup>2</sup>	*
<b>Holzplaster RE</b>				Remark
	<b>SCHÖNOX® PARKETT 600</b> waterless universal SMP adhesive with hard glue-line for parquet	B6	ca. 800 g/m <sup>2</sup>	* Informationen einholen
<b>Hochkantlamelle</b>				Remark
	<b>SCHÖNOX® PARKETT 600</b> waterless universal SMP adhesive with hard glue-line for parquet	B6	ca. 800 g/m <sup>2</sup>	*
	<b>SCHÖNOX® PARKETT 400</b> Wasserfreier Klebstoff für Parkett	B6	ca. 800 g/m <sup>2</sup>	*
<b>2-Schicht-Fertikparkett</b>				Remark
	<b>SCHÖNOX® iLINE®</b> shear-elastic, waterless special adhesive for parquet	SCHÖNOX iLINE APP	ca. 800 g/m <sup>2</sup>	*

	SCHÖNOX® PARKETT 600 waterless universal SMP adhesive with hard glue-line for parquet	B6 - B15	ca. 800 - 1300 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B6 - B15	ca. 800 - 1200 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 250 shear-elastic, waterless special adhesive for parquet	B6 - B15	ca. 850 - 1250 g/m <sup>2</sup>	*
<b>3-Schicht-Fertikparkett</b>				Bemerkungen
	SCHÖNOX® iLINE® shear-elastic, waterless special adhesive for parquet	SCHÖNOX iLINE APP	ca. 800 g/m <sup>2</sup>	*
	SCHÖNOX® iLINE HYBRID	SCHÖNOX iLINE HYBRID AP SCHÖNOX iLINE HYBRID HP	ca. 600 - 650 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 600 waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	ca. 1000 -1300 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B11 - B15	ca. 1000 -1200 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 250 shear-elastic, waterless special adhesive for parquet	B11 - B15	ca. 1050 - 1250 g/m <sup>2</sup>	*
<b>Massivholzdielen</b>				Remark
	SCHÖNOX® iLINE® shear-elastic, waterless special adhesive for parquet	SCHÖNOX iLINE APP	ca. 800 g/m <sup>2</sup>	* Informationen einholen
	SCHÖNOX® iLINE HYBRID	SCHÖNOX iLINE HYBRID AP SCHÖNOX iLINE HYBRID HP	ca. 600 - 650 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 600 waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	ca. 1000 -1300 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B11 - B15	ca. 1000 -1200 g/m <sup>2</sup>	*
<b>Ölhaltige Massivhölzer</b>				Remark
	SCHÖNOX® iLINE® shear-elastic, waterless special adhesive for parquet	SCHÖNOX iLINE APP	ca. 800 g/m <sup>2</sup>	*
	SCHÖNOX® iLINE HYBRID	SCHÖNOX iLINE HYBRID AP SCHÖNOX iLINE HYBRID HP	ca. 600 - 650 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 600 waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	ca. 1000 -1300 g/m <sup>2</sup>	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B11 - B15	ca. 1000 -1200 g/m <sup>2</sup>	*

\* Auf eine möglichst vollflächige Benetzung der Parketrückseite achten. Bei unzureichender Benetzung nächstgrößere Zahnung wählen.

All adhesive fulfill EC1 PLUS acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.lindner-norit.com](http://www.lindner-norit.com).