

## Substrate Preparation

|  |  |  |   |               |
|--|--|--|---|---------------|
| Substrate<br>(for example)               | Mastic asphalt screed acc. to<br>DIN EN 13813 (AS)   | cement based screed acc. to<br>DIN EN 13813 (CT) | Calciumsulfate- or calciumsulfate<br>flowing screed acc. to<br>DIN EN 13813(CA/CAF) | Dry screed    |
| Primer<br>(for example)                  | SCHÖNOX SHP<br>(not necessary if sufficient sanding) | SCHÖNOX VD                                       |   |               |
| Self levelling compound<br>(for example) | SCHÖNOX HS 10<br>SCHÖNOX HS 10 F<br>SCHÖNOX HS 50    |  |   | SCHÖNOX HS 10 |

## Floor Covering Installation

| Covering/ Collection     | Adhesive  | Tool/ trowel acc. TKB | Approx. consumption g/m <sup>2</sup> | Remark   |
|--------------------------|---|-----------------------|--------------------------------------|--|
| <b>PVC</b>               |   |                       |                                      | Range of application   |
| <b>Combo Prime</b>       | <b>SCHÖNOX® DUROCOLL</b><br>Fibre reinforced, strong dispersion<br>adhesive | TKB A1/A2             | approx. 250 - 300 g/m <sup>2</sup>   |  |
| <b>Harmonie Canto</b>    | <b>SCHÖNOX® PU 900</b><br>2-component polyurethane adhesive                 | TKB A2                | approx. 500 g/m <sup>2</sup>         | In wet areas or areas with increase heat developement (like shop windows,<br>winter gardens) |
| <b>ColorWerks</b>        | <b>SCHÖNOX® DUROCOLL</b><br>Fibre reinforced, strong dispersion<br>adhesive | TKB A1/A2             | approx. 250 - 300 g/m <sup>2</sup>   |  |
| <b>TEMPO</b>             | <b>SCHÖNOX® PU 900</b><br>2-component polyurethane adhesive                 | TKB A2                | approx. 500 g/m <sup>2</sup>         | In wet areas or areas with increase heat developement (like shop windows,<br>winter gardens) |
| <b>WOOD CLASSIC PLUS</b> |   |                       |                                      |  |
| <b>LAGOON</b>            |   |                       |                                      |  |

All adhesive fulfill EC1 PLUS acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.swiff-train.com](http://www.swiff-train.com).